



Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

Image shown may not reflect actual configuration

## Specifications

Generator Set Specifications	
Rating (Natural Gas)	50 ekW (62.5 kVA)
Rating (LP Vapor)	50 ekW (62.5 kVA)
Voltage	480,208 Volts
Frequency	60 Hz
Speed	1800 rpm

Generator Set Configurations	
Emissions/Fuel Strategy	U.S. EPA Certified for Stationary Emergency Application

Engine Specifications		
Engine Model	5.7L V8, 4-cycle	
Bore	101.6 mm	4.0 in
Displacement	5.7 L	350 in <sup>3</sup>
Stroke	88.4 mm	3.48 in
Compression Ratio	9.4:1	
Aspiration	Naturally Aspirated	
Governor Type	Electronic	
Fuel Type	Natural Gas, LP Vapor	
Fuel Pressure Operating Range*	2.7 - 3.5 kPa	11 - 14 in. water

Package Dimensions**		
Length	2117 mm	83.3 in
Width	1000 mm	39.4 in
Height	1360 mm	53.5 in
Weight†	920 kg	2028 lb

\*Optional fuel pressure options may be available, please contact your local dealer.

\*\*Note: For reference only – do not use for installation design. Please contact your local dealer for exact weight and dimensions.

†Weight includes: Oversize generator, skid base, circuit breaker, oil, and coolant.

## **Benefits & Features**

### **Generator**

- Matched to the performance and output characteristics of engine
- Industry-leading mechanical and electrical design
- Industry-leading motor starting capabilities
- High efficiency

### **Cat® EMCP Control Panel**

The EMCP 4 controller features the reliability and durability you have come to expect from your Cat equipment. EMCP 4 is a scalable control platform designed to ensure reliable generator set operation, providing extensive information about power output and engine operation. EMCP 4 systems can be further customized to meet your needs through programming and expansion modules.

### **Design Criteria**

- The generator set facilitates compliance with NFPA 110 and meets ISO 8528-5 requirements for transient response
- Cooling system designed to operate in 50°C/122°F ambient temperatures with an air flow restriction of 0.5 in. water

### **UL 2200/CSA – Optional**

- UL 2200 Listed
- CSA Certified

Certain restrictions may apply. Consult with your Cat dealer.

### **Worldwide Product Support**

Cat dealers provide extensive post-sale support including maintenance and repair agreements. Cat dealers have over 1,800 dealer branch stores operating in 200 countries.

## **Standard Equipment**

### **Air Inlet**

- Single element air filter

### **Cooling**

- Radiator and cooling fan complete with protective guards
- Standard ambient temperatures up to 50°C (122°F)

### **Exhaust**

- Exhaust outlet with 3" pipe

### **Fuel**

- Natural Gas or LP Vapor
- Dual lock off valves
- NPT connection

### **Generator**

- Matched to the performance and output characteristics of engine
- IP23 protection
- Integrated Voltage Regulator

### **Governor**

- Electronic governor (non adjustable)

### **Control Panels**

- EMCP 4.2 Series generator set controller

### **Mounting**

- Rubber vibration isolators

### **Starting/Charging**

- 12 volt starting motor
- Batteries with rack and cables

## **Optional Equipment**

### **Generator**

- Excitation: [ ] Permanent Magnet Excited (PM)
- Oversize and premium generators
- Anti Condensation heater

### **Starting/Charging**

- Battery charger – UL Listed 10 amp
- Jacket water heater
- Battery heater
- Lube oil sump heater

### **General**

- UL 2200 Listed
- CSA Certified
- Enclosures: sound attenuated, weather protective
- Automatic transfer switches (ATS)
- Suitable for Use as Service Equipment (SUSE)

**DG50-2**

**50 ekW/ 62.5 kVA/ 60 Hz/ 1800 rpm/ 480V, 208V/ 0.8 Power Factor**

**Rating Type: STANDBY**

**Emissions: U.S. EPA Certified for Stationary Emergency Application**



**DG50-2**  
**50 ekW/ 62.5 kVA**  
**60 Hz/ 1800 rpm/ 480V, 208V**

Image shown may not reflect actual configuration

**Package Performance**

Fuel	Natural Gas	LP Vapor
Generator Set Power Rating with Fan @ 0.8 Power Factor	50 ekW	50 ekW
Generator Set Power Rating	62.5 kVA	62.5 kVA

**Fuel Consumption with Natural Gas**

100% Load With Fan	20.9 m <sup>3</sup> /hr	739 ft <sup>3</sup> /hr
75% Load With Fan	18.1 m <sup>3</sup> /hr	641 ft <sup>3</sup> /hr
50% Load With Fan	13.8 m <sup>3</sup> /hr	489 ft <sup>3</sup> /hr

**Fuel Consumption with LP Vapor**

100% Load With Fan	8.2 m <sup>3</sup> /hr	289 ft <sup>3</sup> /hr
75% Load With Fan	7.0 m <sup>3</sup> /hr	248 ft <sup>3</sup> /hr
50% Load With Fan	5.4 m <sup>3</sup> /hr	192 ft <sup>3</sup> /hr

**Cooling System<sup>1</sup>**

Engine Coolant Capacity	7.8 L	2.1 gal
Radiator Coolant Capacity	8.8 L	2.3 gal
Engine Coolant Capacity with Radiator/Exp Tank	16.6 L	4.4 gal
Air Flow Restriction (System)	0.12 kPa	0.48 in. water

**Inlet Air**

Combustion Air Inlet Flow Rate	4.9 m <sup>3</sup> /min	173 cfm
--------------------------------	-------------------------	---------



**DG50-2**

**50 ekW/ 62.5 kVA/ 60 Hz/ 1800 rpm/ 480V, 208V/ 0.8 Power Factor**

**Rating Type: STANDBY**

**Emissions: U.S. EPA Certified for Stationary Emergency Application**

<b>Exhaust System</b>		
Exhaust Stack Gas Temperature	743°C	1369°F
Exhaust Gas Flow Rate	15.8 m <sup>3</sup> /min	553 cfm
Exhaust System Backpressure (maximum allowable)	10.2 kPa	40.9 in. water

<b>Heat Rejection</b>	<b>480V</b>	<b>208V</b>
Heat Rejection to Coolant (total)	54.9 kW, 3120 Btu/min	
Heat Rejection to Atmosphere from Generator	5.2 kW, 296 Btu/min	4.8 kW, 273 Btu/min

<b>Alternator<sup>2</sup></b>	<b>480V</b>	<b>208V</b>
Motor Starting Capability @ 30% Voltage Dip	131 skVA	128 skVA
Frame	LC1514N	LC1514P
Temperature Rise	130°C	234°F
Excitation	Self Excited	

<b>Lube System</b>		
Sump Refill with Filter	4.7 L	1.24 gal

<b>Emissions (Nominal)<sup>3</sup></b>	
NOx + HC	13.4 g/kW-hr
CO	519 g/kW-hr

<sup>1</sup> For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to the existing restriction from the factory.

<sup>2</sup> Generator temperature rise is based on a 40°C (104°F) ambient per NEMA MG1-32.

<sup>3</sup> The nominal emissions data shown is subject to environment, instrumentation, measurement, facility and engine to engine variations.



Rating Type: **STANDBY**

Emissions: **U.S. EPA Certified for Stationary Emergency Application**

## DEFINITIONS AND CONDITIONS

### Applicable Codes and Standards:

CSA C22.2 No 100-04, UL 489, UL 869, UL 2200, NFPA 37, NFPA 70, NFPA 99, NFPA 110, IBC, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33.

**STANDBY:** Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions.

**Fuel Rates** are based on heat values of 1015 BTU/SCF for Natural Gas and 2500 BTU/SFC for Propane Vapor @77°F (25°C) and 328 ft (100m) above sea level.

Additional ratings may be available for specific customer requirements, contact your Cat representative for details.

Genset Ratings are based on ambient temperature of 77°F and elevation of 1200 ft above sea level.

For higher temperatures and elevations the following derate specifications are to be used:

Altitude: Derate 3.0% per every 1000ft (305 m.) above 1200ft (365 m.)

Temperature: Derate 1.0% per 10°F (5.55°C) temperature above 77°F (25°C)

Feature Code: 57LGE01 Generator  
Arrangement: 467-6050, 467-6051  
Date: 20/01/2019  
Source Country: U.S.

LEHE0998-03 (01/19)

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

©2019 Caterpillar  
All rights reserved.

Materials and specifications are subject to change without notice.  
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, ADEM, S•O•S, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.