



Image shown may not reflect actual configuration

Standby 250 kW 313 kVA – 60 Hz

- UL2200:** Evaluated by ETL to UL Standard for Safety UL2200
- CSA:** Designed in accordance to CSA22.2 standards
- NFPA:** Facilitates compliance with NFPA110
- Type 10:** Product was tested to NFPA110 Type 10

SPECIFICATIONS

Engine		Cooling System	
Engine Model	14.2 L, In-line 6, 4-cycle	Cooling System Type	Pressurized Closed Recovery
Bore x Stroke	135 mm x 165 mm (5.31 in x 6.50 in)	Water Pump Flow – gpm (lpm)	94 (356)
Displacement	14.17 L (864.71 in ³)	Coolant Heater Standard Voltage/Wattage	120 V/1500 W
Compression Ratio	9.5:1	Fuel System	
Aspiration	Turbocharged-Aftercooled	Fuel Type	Natural Gas
Fuel System	Carburetor, Down Draft	Carburetor	Down Draft
Governor	Electronic	Secondary Fuel Regulator	Standard
Fuel Type	Natural Gas	Fuel Shut Off Solenoid	Standard
Emission Certifications	U.S. EPA Certified	Operating Fuel Pressure (Standard)	7" - 11" H ₂ O
Rated Engine Speed	1800 rpm	Engine Electrical System	
General		System Voltage	24 VDC
Cylinder No.	6	Battery Charger Alternator	Standard
Engine Governing		Battery Voltage	(2) 12 VDC
Frequency Regulation (Steady State)	+/- 0.25%		
Lubrication System			
Oil Pump Type	Gear		
Oil Filter Type	Full-flow Cartridge		
Crankcase Capacity – L (qts)	34.3 (36.2)		

ENGINEERED OPTIONS

Engine System	Coolant Heater Ball Valves	Enclosure	Motorized Dampers
	Fluid Containment Pans		Enclosure Ambient Heaters
Alternator System	3rd Breaker Systems	Control System	EMCP 4.2B
			Battery Disconnect Switch
Generator Set	Special Testing		
	Battery Box		

Cat® DG250 GC SPARK-IGNITED GENERATOR SETS

POWER RATINGS – NATURAL GAS

Natural Gas		
Three-Phase 120/208 VAC @0.8pf	250 kW	Amps: 867
Three-Phase 120/240 VAC @0.8pf	250 kW	Amps: 752
Three-Phase 277/480 VAC @0.8pf	250 kW	Amps: 376
Three-Phase 346/600 VAC @0.8pf	250 kW	Amps: 301

STARTING CAPABILITIES (sKVA)

sKVA vs. Voltage Dip													
		480 VAC						208/240 VAC					
Alternator	kW	10%	15%	20%	25%	30%	35%	10%	15%	20%	25%	30%	35%
Standard	250	263	395	527	658	790	922	197	296	395	494	593	692
Upsize 1	300	303	454	605	757	908	1059	227	341	454	568	681	794

FUEL CONSUMPTION RATES*

Natural Gas – ft ³ /hr (m ³ /hr)	
Percent Load	Standby
25%	1044 (29.6)
50%	1790 (50.7)
75%	2417 (68.4)
100%	2983 (84.5)

*Fuel supply installation must accommodate fuel consumption rates at 100% load.

COOLING

		Standby
Air Flow (inlet air combustion and radiator)	ft ³ /min (m ³ /min)	10,078 (285.4)
Coolant System Capacity	gal (Liters)	19 (71.9)
Heat Rejection to Coolant	BTU/hr	788,204
Max. Operating Air Temp on Radiator	°F (°C)	122 (50)
Max. Operating Ambient Temperature (Before Derate)	°F (°C)	104 (40)
Maximum Radiator Backpressure	in H ₂ O	0.5

COMBUSTION AIR REQUIREMENTS

		Standby
Flow at Rated Power	cfm (m ³ /min)	453 (12.8)

ENGINE

		Standby
Rated Engine Speed	rpm	1800
Horsepower at Rated kW**	hp	374
BMEP	psi	190

**Refer to "Emissions Data Sheet" for maximum bhp for EPA and SCAQMD permitting purposes.

EXHAUST

		Standby
Exhaust Flow (Rated Output)	cfm (m ³ /min)	1602 (45.4)
Maximum Recommended Backpressure	inHg	0.75
Exhaust Temp (Rated Output)	°F (°C)	1350 (732)
Exhaust Outlet Size (Open Set)	in	3.5" ID Flex (no muffler)

Deration – For power deration rates reference, please consult Cat LEHE1699-00.