

# Cat® G3516 WITH FAST RESPONSE

## Gas Generator Sets



Image shown may not reflect actual configuration

Bore – mm (in)	170 (6.7)
Stroke – mm (in)	215 (8.5)
Displacement – L (in <sup>3</sup> )	78 (4765)
Compression Ratio	11.5:1
Aspiration	Turbocharged
Fuel System	Electronic Fuel Control Valve
Governor Type	ADEM™ A4

Standby Only 60 Hz kW (kVA) w/Fan	Emissions Performance
1500 (1875)	Non-Certified NOx Selectable (0.5 - 1.0 g/bhp-hr)

### Standard Features

#### Cat® Natural Gas Engine

- Factory Emergency Non-Certified / Site-Performance-Tested version available; meeting a NOx 1.0g/bhp-hr output
- Robust high speed block design provides prolonged life and lower owning and operating costs
- Designed for maximum performance on low pressure gaseous fuel supply

#### Generator Set Package

- Accepts 100% block load in one step and facilitates compliance with NFPA 110, Type 10 starting and loading requirements
- Conforms to ISO 8528-5 G2 load acceptance criteria
- Reliability verified through torsional vibration, fuel consumption, oil consumption, transient performance, and endurance testing

#### Generators

- Superior motor starting capability minimizes need for oversizing generator
- Designed to match performance and output characteristics of Cat engines

#### Cooling System

- Cooling systems available to operate in ambient temperatures up to 43°C (110°F)
- Package tested to ensure proper cooling of complete generator set

#### EMCP 4 Control Panels

- User-friendly interface and navigation
- Scalable system to meet a wide range of installation requirements
- Expansion modules and site specific programming for specific customer requirements

#### Warranty

- 24 months/1000-hour warranty for standby ratings
- 12 months/unlimited hour warranty for continuous ratings
- Extended service protection is available to provide extended coverage options

#### Worldwide Product Support

- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- Your local Cat dealer provides extensive post-sale support, including maintenance and repair agreements

#### Financing

- Caterpillar offers an array of financial products to help you succeed through financial service excellence
- Options include loans, finance lease, operating lease, working capital, and revolving line of credit
- Contact your local Cat dealer for availability in your region

## Optional Equipment

### Engine

#### **Air Cleaner (Single Element)**

- ☐ Installed
- ☐ Supplied loose

#### **Muffler**

- ☐ Industrial grade (15 dB)
- ☐ Residential grade (18 dB)
- ☐ Critical grade (25 dB)
- ☐ Spark arresting

#### **Starting**

- ☐ Standard batteries
- ☐ Standard electric starter(s)
- ☐ Air starter(s)
- ☐ Jacket water heater

### Generators

#### **Output voltage**

- ☐ 440V
- ☐ 480V
- ☐ 600V
- ☐ 4160V

#### **Temperature Rise (over 40°C)**

- ☐ 150°C      ☐ 80°C
- ☐ 125°C/130°C

#### **Winding type**

- ☐ Random wound
- ☐ Form wound

#### **Excitation**

- ☐ Permanent magnet (PM)

#### **Attachments**

- ☐ Anti-condensation heater
- ☐ Stator and bearing temperature monitoring and protection

#### **Radiator**

- ☐ Factory Provided (1.5MW Only)
- ☐ Dealer / Customer Provided

### Power Termination

#### **Type**

- ☐ Bus bar
- ☐ Circuit breaker
- ☐ 400A      ☐ 800A
- ☐ 1200A   ☐ 1600A
- ☐ 2000A   ☐ 2500A
- ☐ 3200A   ☐ 4000A
- ☐ UL      ☐ IEC
- ☐ 3-pole   ☐ 4-pole
- ☐ Manually operated

- ☐ Electrically operated

#### **Trip Unit**

- ☐ LSI
- ☐ LSI-G
- ☐ LSIG-P

### Enclosure

- ☐ Weather protective
- ☐ Sound attenuated

#### **Attachments**

- ☐ Cold weather bundle
- ☐ DC lighting package
- ☐ AC lighting package
- ☐ Motorized louvers

### Fuel System Pressure

- ☐ Standard
- ☐ Low

### Control System

#### **Controller**

- ☐ EMCP 4.3
- ☐ EMCP 4.4

#### **Attachments**

- ☐ Local annunciator module
- ☐ Remote annunciator module
- ☐ Load share module
- ☐ Remote monitoring software

### Charging

- ☐ Battery charger – 20A
- ☐ Battery charger – 35A
- ☐ Battery charger – 50A

### Vibration Isolators

- ☐ Rubber
- ☐ Spring
- ☐ Seismic rated

### Cat Connect

#### **Connectivity**

- ☐ Ethernet

### Extended Service Options

#### **Terms**

- ☐ 2 year
- ☐ 3 year
- ☐ 5 year
- ☐ 10 year

#### **Coverage**

- ☐ Silver
- ☐ Gold
- ☐ Platinum
- ☐ Platinum Plus

### Ancillary Equipment

- ☐ Automatic transfer switch (ATS)
- ☐ Uninterruptible power supply (UPS)
- ☐ Paralleling switchgear
- ☐ Paralleling controls

### Certifications


- ☐ UL 2200 Listed
- ☐ CSA Certified

**Note:** Some options may not be available on all models. Certifications may not be available with all model configurations. Consult factory for availability.

## Package Performance

Performance		Standby	
Frequency		60 Hz	
Genset power rating @ 0.8 power factor – ekW (kVA)		1500 (1875kVA)	
Emissions		NOx Selectable - 1.0 g/bhp-hr	
Performance number		EM6086 w/fan	
Fuel Consumption			
100% load with fan – MJ/ekW-hr (Btu/ekW-hr)		10.24	(9356)
75% load with fan – MJ/ekW-hr (Btu/ekW-hr)		10.88	(9846)
50% load with fan – MJ/ekW-hr (Btu/ekW-hr)		12.23	(10909)
Cooling System			
Radiator air flow restriction – kPa (in. water)		0.12	(0.5)
Radiator air flow – m³/min (cfm)		2146	(75784)
Radiator ambient capability @ 304 m (1000 ft) – °C (°F)		45	(113)
Auxiliary circuit temperature (maximum inlet) – °C (°F)		54	(130)
Jacket water temperature (maximum outlet) – °C (°F)		99	(210)
Inlet Air			
Combustion air inlet flow rate – Nm³/bkW-hr (ft3/min)		4.26	(4621)
Altitude Capability			
At 25°C (77°F) ambient, above sea level – m (ft)		2000	(6562)
Exhaust System			
Exhaust temperature – engine outlet – °C (°F)		509	(949)
Exhaust Gas Flow – Nm³/bkW-hr (ft³/min)		4.53	(13072)
Exhaust Gas Mass Flow – kg/bkW-hr (lb/hr)		5.71	(21239)
Heat Rejection			
Heat rejection to jacket water circuit (JW+AC1+OC) – kW (Btu/min)		927	(52726)
Heat rejection to jacket water – kW (Btu/min)		549	(31230)
Heat rejection to exhaust (LHV to 120°C/248°F) – kW (Btu/min)		1175	(66821)
Heat rejection to auxiliary circuit – kW (Btu/min)		151	(8583)
Heat rejection to atmosphere from engine and generator – kW (Btu/min)		205	(11638)

## Weights and Dimensions



Dim "A" mm (in)	Dim "B" mm (in)	Dim "C" mm (in)	Dry Weight kg (lb)
7000 (275.6)	2345 (92.3)	3265 (128.5)	14,314 (31,557)

**Note:** For reference only. Do not use for installation design. Contact your local Cat dealer for precise weights and dimensions.

## Ratings Definitions

### Standby

Output available with varying load for the duration of an emergency outage. Average power output is 100% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

### Continuous

Output available with non-varying load for unlimited time. Average power output is 70-100% of the continuous power rating. Typical peak demand is 100% of continuous rating for 100% of the operating hours.

### Applicable Codes and Standards

AS 1359, CSA C22.2 No. 100-04, UL 489, UL 869, UL 2200, NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC 60034-1, ISO 3046, ISO 8528, NEMA MG1-22, NEMA MG1-33, 2014/35/EU, 2006/42/EC, 2014/30/EU.

**Note:** Codes may not be available in all model configurations. Please consult your local Cat dealer for availability.

### Fuel Rates

- For transient response, ambient, and altitude capabilities consult your local Cat dealer.
- Fuel pressure range specified is to the engine fuel control valve. Additional fuel train components may be required and should be considered in pressure and flow calculations.
- For a complete reference of definitions and conditions see the following data sheets
  - 1500ekW Standby / Emergency: EPA Certified EM6085 w/fan, EM6081 w/o fan
  - 1500ekW Standby / Emergency: Non-Certified 0.5g EM6087 w/fan, EM6083 w/o fan
  - 1500ekW Standby / Emergency: Non-Certified 1.0g EM6086 w/fan, EM6082 w/o fan

[www.cat.com/electricpower](http://www.cat.com/electricpower)

©2022 Caterpillar  
 All rights reserved.

Materials and specifications are subject to change without notice.  
 The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission